



**Traffic Logix Corporation**  
 3 Harriett Lane  
 Spring Valley, NY 10977 USA  
**Tel:** (866) 915-6449  
**Fax:** (844) 405-6449  
[www.trafficlogix.com](http://www.trafficlogix.com)

Quote Number QUO-38188-C7D7B3  
 Created Date 6/12/2024  
 Expiration Date 7/12/2024  
 Prepared by Jim Entwistle

**QUOTATION**

**Contact: Chris Spolnik**  
 Phone: 219-712-8754  
 Email: [cspolnik@munster.org](mailto:cspolnik@munster.org)

**Town of Munster, IN**

**Shipping Address:**  
 508 Fisher St  
 Munster, Indiana 46321  
 United States

**Standard Features (Included)**

- Prices Shown include - Required Adhesive, Bolts and Anchors (Specified as 4" or 7") 7"
- Color and Markings as Indicated: MUTCD Arrows

**Special Notes**

**Quote Line Items – All Prices shown are in \$ US Dollar**

Product	Product Code	Quantity	Sales Price	Total Price
14Lx6Wx3" speed cushion with arrows	SC146A	10.00000	\$1,616.00	\$16,160.00
400mL 1:1 Dispenser - Adhesive Applicator Gun	PU-APGUN	1.00000	\$65.00	\$65.00
SDS-Plus Shank Rotary-Hammer Drill Bit.9/16"Bit, 16 Drilling Depth, 18-3/4" Overall Length.	23596	1.00000	\$65.00	\$65.00

**Totals**

Subtotal: \$16,290.00  
 Freight: \$940.00  
 Sales Tax (if applicable): \$0.00  
**Grand Total: \$17,230.00**

**Terms:** 1% - 10 days – Net 30

**Payment:** MC, VISA, AMEX. Credit card payments over \$10K will include an additional 2% fee.



**Traffic Logix Corporation**  
3 Harriett Lane  
Spring Valley, NY 10977 USA  
**Tel:** (866) 915-6449  
**Fax:** (844) 405-6449  
[www.trafficlogix.com](http://www.trafficlogix.com)

Quote Number QUO-38188-C7D7B3  
Created Date 6/12/2024  
Expiration Date 7/12/2024  
Prepared by Jim Entwistle

**Tax: IF TAX EXEMPT,** Please Provide Tax Exempt Certificate with Order

**Freight:** Freight quotation is valid for a period of 21 days after it is issued. Beyond that, freight quotations will require confirmation or adjustment.

**Changes/Returns:** 30% for standard orders and 50% on custom orders.

**Warranty:** Please refer to the Rubber conditional use warranty terms at the end of this quote.

### Delivery Requirements

Please Indicate the availability of the following as this determines the freight costs:

1. Do You have a Loading Dock? - Yes/No
2. Do you have a Forklift and Pallet Jack to unload? - Yes/No
3. Can access be gained by a 53-foot truck for delivery? - Yes/No
4. Is the delivery address a Construction site? - Yes/No
5. Is the delivery address a Military site? - Yes/No
6. If shipping to Military site, is a U.S. Driver required? - Yes/No

### Quote Acceptance Information

Signature \_\_\_\_\_  
Name \_\_\_\_\_  
Title \_\_\_\_\_  
Date \_\_\_\_\_

**Thank you for choosing Traffic Logix. Please sign and return to:**

jentwistle@trafficlogix.com  
Jim Entwistle  
Regional Sales Manager  
+12177411639

**Please complete to set up new account:** <https://trafficlogix.com/business-application-form/>

## RUBBER CONDITIONAL USE WARRANTY



### Conditional Use Terms Rubber Traffic Calming Devices

1. Traffic Logix traffic calming devices (the "Traffic Calming Products") are designed to be installed on local residential streets with posted speeds of 35 mph or less. Prior to installation, the Customer should determine if any federal, state, or local regulations govern the installation or use of Traffic Calming Products.
2. The installation location of any Traffic Calming Product should be reviewed by a Traffic Engineer.
3. Traffic Calming Products should only be used on roads with less than 5,000 vehicles per day.
4. Traffic Calming Products should be installed only on roads that are used primarily by passenger vehicles and/or emergency response vehicles with the roads themselves in respectable condition.
5. Traffic Calming Products should be installed in such a way that they are visible from at least 200 feet. For safe usage, Traffic Logix products must be installed in conjunction with appropriate signage in accordance with ITE's State of the Practice on Traffic Calming, as well as ITE's Manual on Uniformed Traffic Control Devices.
6. Traffic Calming Products should not be installed on roadways that have more than an 8% grade.
7. Traffic Calming Products should be installed with a minimum of three inches of asphalt or concrete underneath the device.
8. All bolts and anchors provided with product must be installed as instructed, and with Traffic Logix anchor adhesive that is also included with each product.
9. Quarterly inspection of each Traffic Calming Product is required. If the Traffic Calming Product has been damaged in any way, it should be replaced.
10. Traffic Logix Products should be removed prior to the first snowfall and should only be reinstalled in non-winter months.

