



Conditional Use Terms Rubber Traffic Calming Devices

1. Traffic Logix traffic calming devices (the “Traffic Calming Products”) are designed to be installed on local residential streets with posted speeds of 35 mph or less. Prior to installation, the Customer should determine if any federal, state, or local regulations govern the installation or use of Traffic Calming Products.
2. The installation location of any Traffic Calming Product should be reviewed by a Traffic Engineer.
3. Traffic Calming Products should only be used on roads with less than 5,000 vehicles per day.
4. Traffic Calming Products should be installed only on roads that are used primarily by passenger vehicles and/or emergency response vehicles with the roads themselves in respectable condition.
5. Traffic Calming Products should be installed in such a way that they are visible from at least 200 feet. For safe usage, Traffic Logix products must be installed in conjunction with appropriate signage in accordance with ITE’s State of the Practice on Traffic Calming, as well as ITE’s Manual on Uniformed Traffic Control Devices.
6. Traffic Calming Products should not be installed on roadways that have more than an 8% grade.
7. Traffic Calming Products should be installed with a minimum of three inches of asphalt or concrete underneath the device.
8. All bolts and anchors provided with product must be installed as instructed, and with Traffic Logix anchor adhesive that is also included with each product.
9. Quarterly inspection of each Traffic Calming Product is required. If the Traffic Calming Product has been damaged in any way, it should be replaced.
10. Traffic Logix Products should be removed prior to the first snowfall and should only be reinstalled in non-winter months.

